

RØDE NT3

Features

- Transformerless output
- Internal capsule shock mounting
- Heavy duty Cast metal/satin nickel body
- High immunity to RF interference
 - High strength welded and heat treated mesh head
 - Premium quality surface mount components
- True condenser (externally biased)
 - Hypercardioid polar response
 - Full frequency response
 - Battery status LED indicator
 - 12 months parts and labour guarantee



NT3

Stylish and modern, the NT3 is the latest in microphone technology Purpose built for studio, stage and location work.

The NT3 is made from the finest components to deliver results demanded by engineers and musicians alike.

The NT3 features battery and phantom power and its low noise makes it hard to match.

The Rode NT3 - when superior sound quality is demanded.

Specifications

Accessories included:

- Zip pouch
- Wind Shield
- Stand Mount with 3 /8"-5/8" Thread Adaptor



Capsule: Externally polarised 19mm (3/4") condenser
Active Electronics: JFET impedance converter with bipolar output buffer
Pickup Pattern: Hypercardioid (see graph)
Frequency response: 20 Hz-20 kHz
Output Impedance: 200 Sensitivity: -39dB re 1volt/pascal (12mV @ 94dB SPL) +/- 2dB
Equivalent Noise: <17 dBA (A-weighted per IEC268-15)
Maximum Output: +9.5dBu (@ 1% THD into 1K)
Dynamic Range: > 123dB (per IEC268-15)
Maximum SPL: > 140dB SPL (@ 1% THD into 1K) Signal/Noise Ratio: > 77dB (per IEC268-15)
Power Requirements: P48, P24, P12 phantom 9V battery Packed Weight 680g (Mic only no battery 371g)

info@rodemicrophones.com